Z12NK2 KU-BAND COMMUNICATION

The SuperTrack Z-Series is the perfect solution for ships looking for broadband speeds at sea. Stay in touch with your networks via high speed access to the internet, email, multiple VoIP phones and more.



Z _SERIES

STANDARD FEATURES

- Automatic Satellite Search & Skew Control
- Unlimited Azimuth Uninterrupted searching keep you in business however you ship turns Cable wrap free
- Brake System
- Accurate Signal Acquisition by KNS's Distinctive Algorithm
- Pre-programmed Satellite Database Editable 80 satellite data
- Antenna Control Unit 3 Types of Gyro Input (NMEA, Synchro, Step by Step)
- CE R&TTE Certified
- Intelsat Qualified

ABOVE DECK

Dish Diameter Antenna Dimension Antenna Weight Radome Material Frequency

Antenna Gain

G / T

Operating Platform LNB BUC Skew Control Elevation Angle Azimuth Range Cross Angle Ship Motion

Tracking Speed Vibration Damper Temperature Humidity Antenna Input Power

DECK

120cm(49") 161cm(D) x 163cm(H) 142 Kg Honeycomb FRP TX : 13.75 ~ 14.5 GHz RX : 10.7 ~ 12.75 GHz TX : 42.87 dBi @ 14.25 GHz RX : 40.95 dBi @ 11.75 GHz 20.79 dB/K (in Radome) @ 30deg. Elevation angle and 11.75GHz, Clear Sky

3 - Axis Single PLL LNB / Universal LNB(optional) 4W / 6W / 8W / 16W / 25W / 40W (optional) Automatic -20° to +110° Unlimited ± 35° Roll : ±24° at 8-12 sec periods Pitch : ±14° at 6-12 sec periods Yaw : ±8° at 15-20 sec periods More than 90°/sec Wire Rope Isolator Included -20°C to +55°C Up to 100% @ 40°C TX: 48V DC, 3.2A RX: 48V DC, 4.18A

BELOW DECK

ACU Size Gyro Interface Input Power Output Power External I/O

19" Rack 1U size NMEA 0183, Synchro, Step by Step 100 ~ 120V AC / 200 ~ 240V AC, 50/60Hz, 8A/4A TX : 48V DC, 3.2A RX : 48V DC, 4.18A RS-232C, Mini-USB, Ethernet, Console

PACKING

Size Gross Weight Packed by Certification/ Qualification 174 x 174 x 190 cm 310Kg Wooden Crate **(€0678** MIL-STD-167)

WARRANTY INFORMATION

KNS offers 3-year parts, 1-year onboard labour warranty for the SuperTrack series

* This Specification can be changed without notice.

